



Solar Flare[®]

Hassle Free Mobile Light Towers

Tel: 1300 444422
www.liftequipt.com.au



Solar Lighting System - Skid Mount

Dimension & Weight:

LE1200A-S	Dimensions (mm)	Weight (Kg)
	2500*2100*3200	1580kg

Shipping Loading:

System Parameter:	
Run Time	20 hours
Charge Time	10 hours
System Voltage	DC24V
Wind Rating Speed	100KPH
Protection Level	IP65
Solar System:	
No. of Solar Panel	4
Panel Wattage	380W
Panel Output	1520W
Panel Material	Monocrystal Silicon
Solar Controller	MPPT Solar Charge Controller
Battery:	
No. of Battery	8 x 150Ah
Capacity	600AH, DC24V
Material	Gel Type Lead Acid
Battery Charger	Included
Lamp:	
Type of Lamp	LED Lamps
Lamp No.	6
Lamp Wattage	100W, DC24V per pc
Total Lumens	90,000
Lights Tilt and Rotation:	
Tilt	Electrical Motor
Rotation	Electrical Pan
Mast Tower:	
Type	Manual Mast
Total Height	9M
Operate for Extend and Lower	Manual Operation
Rotation	360 Degrees Bottom Rotation
Skid:	
Chassis	High Strength Skid Chassis
Forklift Pockets	150*250*2000mm
Fire Extinguisher	Included
Insulation Foam	Inside Tower Enclosure
Paint	Powder coat to prevent corrosion