

Product Feature:

1. 4*330W solar panels
2. 4x200Ah/6x150Ah/8x150Ah gel batteries, DC24V/DC48V system
3. Optional 6 to 9 meters manual/electric/hydraulic mast
4. Single axle trailer with Australia/North America standard
5. Widely used in CCTV security, communication, lighting etc



TECH SPECS:

TOWER DIMENSIONS

Length:	4100mm
Width:	2100mm
Height:	2520mm
Weight:	1400kg

MAST DETAILS

Mast Raise/Extension:	Manual/Electric/Hydraulic
Safety:	Auto Lock/Sensor/Safety Valve
Mast Height(m):	Optional
Mast 360 Degrees:	Optional
Coil Cable:	Optional
Wind Rating Speed:	100km/h

TRAILER DETAILS

Trailer Type:	Single Axle
Tire and Rim Size:	15"
Stabalizer Supports:	4xManual
Drawbar:	A Frame
Tow Hitch:	50mm Ball/70mm Ring
Mud Guard/Wheel Chock:	Special Design
Backup Generator:	Optional
Working Temperature(°C):	-35~60

SELECTION TABLE:

Code	Solar Panel(W)	Mast(M)	Battery(Ah)	Generator(Kw)	Trailer Standard		
LE1200A	4*330W (fixed angle)	MM (manual mast)	6	B800(4*200Ah) B900(6*150Ah)	D3(diesel 3kW) D5(diesel 5kW) G3(gasoline 3kW)	AU/US/EU	EB(electric brake) MB(mechanical brake)
			7.5				
			9				
		EM (electric mast)	6	B1200(8*150Ah)	N/A		
			7.5				
			9				
		HM (hydraulic mast)	6	B800(4*200Ah) B900(6*150Ah) B1200(8*150Ah)	N/A		
			7.5				
			9				

ORDER

Code	Mast	Battery	Generator	Trailer Standard
LE 1200A	-EM9	-B900	-D5	-US-EB